

FERENTINO CONVENTIONAL PNEUMATIC FOR SMALL - SIZED MACHINES

PNEUMATIC

SS



SD



SKZ+



NM
non marking

SS

- Standard tread with sidewall properties.
- Good traction.

SD

- Resistant tread reinforced in the middle.
- Compound resistant to punctures.
- Balanced tread wear.
- Reinforced sidewalls.

SKZ+

- Sturdy tyres for extreme condition.
- High pattern: improves performance and tyre life.
- Good self- cleaning properties.



FERENTINO CONVENTIONAL PNEUMATIC

PNEUMATIC

CODE	TIRE SIZE	PROFILE	PR	TYPE	RIM WIDTH	INFLATION PRESSURE ETRTO (bar)	OVERALL DIAMETER (mm) ± 2%	OVERALL SECTION WIDTH (mm) ± 2%	LOAD CAPACITY (kg)		WEIGHT(kg)	
									8 km/h	16 km/h	Kg	Pound
	6.70 - 12	SD	6	TL	4.60	4.10	670	146	660	520	7.90	17.38
	23x8.60 - 12	SS	6	TL	7.0	3.40	675	215	820	660	12.70	27.94
	27x8.60 - 15	SS	8	TL	7.0	4.80	680	210	1.250	990	16.20	33.44
	27 x 10.60 - 15	SS	8	TL	8.50	3.50	700	260	1.280	1.010	18.10	39.82
	10x16.5	SS	10	TL	8.25	5.10	775	280	2.135	1.685	22.70	49.94
	10x16.5	SKZ +	10	TL	8.25	5.20	773	264	2.135	1.685	20.20	44.44
	12x16.5	SS	12	TL	9.75	5.60	845	330	2.890	2.285	36.60	80.52
	12x16.5	SKZ +	12	TL	9.75	5.60	831	307	2.890	2.285	40.20	88.44