

MULTI-PURPOSE CONVENTIONAL PNEUMATIC FOR MANUFACTURING MACHINES

PNEUMATIC

MT63

MT45

MT54

MT72

MT90



NM
non marking

MT63

- Tread for on/off - road application.
- Good traction.

Applications:

Municipality vehicle used on roads.
Agricultural vehicles.
Special service vehicles.

MT45

- Tread with good traction and self - cleaning properties for on/off - road applications.
- Good stability and manoeuvrability.

MT54

- Multi purpose tread with excellent pattern for special applications.
- Good traction and self-cleaning properties.

MT72

- Tread especially suitable for loader applications.
- Good traction and self-cleaning properties.

MT90

- Tread with good traction characteristics and increased stability.
- Suitable for excavators and telescopic hoisting devices.



FERENTINO MULTI-PURPOSE CONVENTIONAL PNEUMATIC

PNEUMATIC

CODE	TIRE SIZE	PROFILE	PR	TYPE	RIM WIDTH	INFLATION PRESSURE ETRTO (bar)	OVERALL DIAMETER (mm) ± 2%	OVERALL SECTION WIDTH (mm) ± 2%	LOAD CAPACITY (kg) 40 km/h	WEIGHT(kg)	
										Kg	Pound
	10.6/80-18	MT45	10	TL	9.00	3.70	910	280	1.950	31.90	70.18
	12.6/80-18	MT45	12	TL	W9	3.70	990	310	2.650	42.10	92.62
	18-19.5	MT63	18	TL	14.00	6.75	1.090	465	6.605	75.00	166.00
	10.6-20	MT64	10	TL	9.00	3.75	960	275	2.070	31.80	69.96
	12.6-20	MT64	12	TL	11.00	3.60	1.055	330	2.300	48.80	107.36
	14.6-20	MT64	14	TL	11.00	3.60	1.095	355	2.795	68.40	128.48
	406/70-20	MT64	14	TL	13.00	3.60	1.090	385	3.335	60.60	133.10
	406/70-20	MT72	14	TL	13.00	3.60	1.150	405	3.335	67.20	147.84
	18-22.5										
	406/70-24	MT64	14	TL	13.00	3.60	1.190	415	3.620	76.00	167.20
	406/70-24										

MT54

- Classical tread with excellent pattern for all applications.
- Good traction and self-cleaning properties.



FERENTINO MULTI-PURPOSE CONVENTIONAL PNEUMATIC

PNEUMATIC

CODE	TIRE SIZE	PROFILE	PR	TYPE	RIM WIDTH	INFLATION PRESSURE ETRTO (bar)	OVERALL DIAMETER (mm) ± 2%	OVERALL SECTION WIDTH (mm) ± 2%	LOAD CAPACITY (kg) 40 km/h	WEIGHT(kg)	
										Kg	Pound
	8.25-20	MT54	14	TT	6.5-20	6.75	970	232	2.180	35.00	77.00
	9.00-20	MT54	14	TT	7.0-20	7.00	1.012	256	2.660	43.00	94.60
	10.00-20	MT54	16	TT	7.5-20	7.50	1.050	280	3.190	50.00	110.00